



Installation Tips

-EUROFLOOR solid hardwood flooring is appropriate for installation in all residential areas on and above ground level.

-EUROFLOOR is not recommend it for below grade as it is very difficult to control humidity on this level and flooring may be affected by moisture.

-EUROFLOOR solid hardwood flooring is not recommended for installation over radiant heated floors.

-EUROFLOOR solid hardwood flooring may be nailed down with cleats or staples over wooden subfloor.

Before you start installation make sure the following pre-installation requirements are met:

1. Hardwood flooring should be one of the last items installed during renovation to avoid damage.
2. Prior to installation heating and air conditioning systems must be in operation and room temperature must have been maintained at 18-22C for at least one week.
3. Relative humidity on job site should be 45-55% at all times.
4. To avoid moisture- related damages subfloor must be dry and basement well ventilated. Moisture level of wood subfloor must not exceed 12% and differential between wood planks and subfloor must be less than 4%.
5. Flooring must be acclimated on the job site under occupancy conditions for four to five days before installation. For acclimation flooring must be wrapped and cartons must be opened.

Remember that owners and installer are jointly responsible and must make sure that all pre-installation requirements are met.

EUROFLOOR hardwood flooring is manufactured to exceed established industry quality standards that permit a defect tolerance and grading variance up to 5%. Each and every piece of EUROFLOOR flooring is subject to scrupulous factory inspection. However, final pre-installation approval has to be done by owner and (or) installer. Installer must inspect every piece before installation.

Once nailed down, the plank is considered accepted. EUROFLOOR's responsibility is limited to the replacement (material only) of defective products in excess of 5% norm.

Installation procedure requires certain experience and we highly recommend that professional installers do the job. Contact EUROFLOOR dealer for installation.