Use the soap recommended by the manufacturer. It's a natural oils based product for the maintenance of oiled wood floors. The soap cleans, nourishes the wood and increases the water-repellency of your floor.

CLEANING AFTER INSTALLATION

Following the installation of your pre-oiled floor, we strongly recommend that you do the following steps:

- Sweep or vacuum.
- Complete cleaning with water only (well wrung mop) to remove as much construction / renovation dust as possible
- Complete cleaning with water and the amount of soap indicated on the back of the soap bottle in your starting kit.

FOR REGULAR USE

- Mix 4 or 5 caps of osmo floor soap or any other manufacturer approved Flooring Soap with 10 liters of water.
- Apply with a mop, in the direction of the wood grain.
- Wring out the dirty mop and rinse it in a second bucket with clean water.
- Dry cleaning is the best way to clean hardwood floors, rather than wet cleaning.

IMPORTANT

Please read the instructions before using the soap. Using the right soap maintains the characteristics of your pre-oiled floor finish.

WARNING

some cleaning products sold in supermarkets may damage the finish of your floor (e.g.: Hertel, Vim, Mr Net, Murphy soaps ...), we recommend the use of our soaps at all times. Floors can be freshened up with maintenance oil when the wood floor becomes hard to clean or if the surface gets scratched or dull. If you see changes in the look of your floor don't wait and call us. Its always better to maintain than to repair.